

LAM 3G

VISIBLE / INFRARED LASER AIMER



LAM 3G VISIBLE/INFRARED LASER AIMER



The LAM 3G is a multi-laser aiming system equipped with collimated visible and IR lasers designed to reach out to 2,000m. Built-in IR illuminator and IR aiming laser provide covert tactical precision when paired with night vision devices. Features an adjustable IR illuminator for better illumination at longer ranges, dual activation switches and high/low power modes ensures appropriate laser intensity during training exercises. With a quick-release M1913 mount, LAM 3G is amongst the lightest aimers in its class and is the right choice for professional operators demanding unrivalled performance and reliability. The unit is constructed of high-strength aluminum and can withstand rigors of tactical life on virtually any weapon platform.

| Visible Laser Aimer | LAM 3G |
|--|--------------|
| Eye safety | IIIb |
| Distance, low/high (m) | 150 / 500 |
| Beam divergence, FWHM (mrad) | 0.5 |
| Spot size @ 100m (mm) | 50 |
| Wavelength (nm) | 532 ±10 |
| Laser colour | Green |
| Output power, low/high (mW) | <4/≥8 |
| Infrared Laser Aimer | |
| Eye safety | IIIb |
| Distance, low/high (m) | 400 / 2,000 |
| Beam divergence, FWHM (mrad) | 0.5 |
| Spot size @ 100m (mm) | 50 |
| Wavelength (nm) | 830 ±15 |
| Output power, low/high (mW) | <2/≥20 |
| Infrared Laser Illuminator | |
| Eye safety | IIIb |
| Distance, low/high (m) | 200 / 2,000 |
| Beam divergence, FWHM (mrad) | 1 - 105 |
| Wavelength (nm) | 830 ±15 |
| Output power, low/high (mW) | <2/≥25 |
| Ballistics | |
| Windage adjustment step (mrad) | 0.25 |
| Windage adjustment range (mrad) | 60 |
| Elevation adjustment step (mrad) | 0.25 |
| Elevation adjustment range (mrad) | 60 |
| Retention after 1,000 shots (mrad) | 1 |
| Mechanics, Electronics & Environmental | |
| Dimensions (mm) | 105x86x48 |
| Weight without batteries (g) | 315 |
| Weight with batteries (g) | 330 |
| Shock resistance (G) | 300 |
| Quick release | Yes |
| Battery type | CR 123 |
| Battery life, high/low (hours) | 8 / 16 |
| Operating temperature range (°C) | -20 to +50 |
| Storage temperature range (°C) | -40 to +60 |
| Waterproofing | MIL-STD 810G |

LAM 3G

VISIBLE / INFRARED LASER AIMER



DELIVERY SET

Supplied with the following standard accessories:

- Soft carrying case
- Pressure switch membrane for remote operation
- 1x CR 123 Lithium battery
- Operation Manual

ACCESSORIES



Optional Hard Case



Delivery Set



Side View



Mounted on Scar Rifle

LAM 3G VISIBLE / INFRARED LASER AIMER